

**technical details IC100 series**



	<b>weight</b>	<b>working length</b>	<b>Netz</b>	<b>Fuse</b>
<b>IC100-1300</b>	29Kg	1280mm	210V-230V 50/60Hz 330W	Fuse 5x20 1,6AT
<b>IC100-2200</b>	54Kg	2180mm	210V-230V 50/60Hz 860W	Fuse 5x20 3,4AT

Europa	
UL-Version USA	
SASO middle east	 220 V 13 A

	IC100-1300	IC100-2200
Detachable end stop from 12 to 300 mm	x	
Side lay	x	x
Digital temperature display	x	x
Temperature is infinitely adjustable	x	x
Heating wire is adjustable from - 8 to 20 mm	x	x
User manual	x	x

<b>material</b>	<b>bending-temperature</b>	<b>Max thickness</b>
ABS	100°C to 150°C	5mm
PC	150°C to 210°C	5mm
PMMA (Acryl)	120°C to 170°C	6mm
PS	100°C to 150°C	6mm
PVC-hard	110°C to 140°C	6mm
PET	120°C to 160°C	8mm

Packing 12mm OSB woodbox				
IC100-1300	Ca. 40kg	1524mm	644mm	254mm
IC100-2200	Ca. 60Kg	2424mm	644mm	254mm

